



HA-TRCAM02



Intelligent Trail Camera

Specification 1



Feature

- Built-in 2G, 3G, 4G GSM wireless image transmission function, SMS / MMS / E-mail
- Support daily report SMS notification
- Support four frequency band quad-band: 850/900/1800/1900mhz.
- With 1/3" high definition 5MP image sensor, Low illumination:0.1Lux (LED off)
- 6.0mm fixed lens. (H FOV=78°, F2.0)
- Photo definition can be optional with 12M/8M/5M/3M/2M/1M
- 1080P/30fps full HD video recording
- Support USB data connection and PC fast parameter settings.
- Support external power supply or solar power, to provide longer working hours.
- Support dismantling chains, protection lock and password protection function, to protect the camera safety.
- Support limit setup for daily shoot numbers.
- Support low power alert.
- Support SD card with maximum capacity of 32G.
- Support the laser alignment, to make more convenient installation.

Model	HA-TRCAM02
Image Sensor	5Mega pixel 1/3 "HD color CMOS
Sensitivity	0.005 Luk / F1.2 / 30IRE (LED off)
Effective pixels	2560x1920 / 4915.2K
Photo Definition	12M/8M/5M/2M/1M
Shooting No	1~5
Video Definition	1920x1080/30 fps
Video length	1~120s
Lens	
Lens	6mm HD Fixed Lens
Trigger time	<0.8 Sec
Photo+Video	First photo, then video
Max-Shooting	Support, 0~255, 0 means no limit.
View photo and video	Support thumbnail, 16 times enlargement support video playing, support advanceX2/X4, reteat X2/X4
Display Screen	
Display Screen	2.0 "LCD Screen; definition: 960x480; 16.7M color
Audio	
Microphone	60dB High Sensitivity Sound Collection
Loudspraker	0.5 (8Ω) Hi-Fi Loudspeaker
Audio record	ON/OFF
Boot Sound	ON/OFF
Key Sound	ON/OFF
PIR	
PIR Sensing Angle	Main PIR:50°, 8 zone, each zone 10° Side PIR: Left and right light beams form An angle of 140° left and right of the five zone, each zone 10°
PIR Sensor Distance	20M (at 10°C)
PIR Mode	Main PIR / Main PIR & Side PIR / OFF
PIR Sensitivity	Auto/low/normal/high
Trigger Interval	5-59sec, 1-59min Programmable

HA-TRCAM02

Specification 2



Feature

- Built-in 2G, 3G, 4G GSM wireless image transmission function, SMS / MMS / E-mail
- Support daily report SMS notification
- Support four frequency band quad-band: 850/900/1800/1900mhz.
- With 1/3" high definition 5MP image sensor, Low illumination:0.1Lux (LED off)
- 6.0mm fixed lens. (H FOV=78°, F2.0)
- Photo definition can be optional with 12M/8M/5M/3M/2M/1M
- 1080P/30fps full HD video recording
- Support USB data connection and PC fast parameter settings.
- Support external power supply or solar power, to provide longer working hours.
- Support dismantling chains, protection lock and password protection function, to protect the camera safety.
- Support limit setup for daily shoot numbers.
- Support low power alert.
- Support SD card with maximum capacity of 32G.
- Support the laser alignment, to make more convenient installation.

Model	HA-TRCAM02
Image Sensor	5Mega pixel 1/3 "HD color CMOS
Sensitivity	0.005 Luk / F1.2 / 30IRE (LED off)
Effective pixels	2560x1920 / 4915.2K
Photo Definition	12M/8M/5M/2M/1M
Shooting No	1~5
Video Definition	1920x1080/30 fps
Video length	1~120s
Lens	
Lens	6mm HD Fixed Lens
Trigger time	<0.8 Sec
Photo+Video	First photo, then video
Max-Shooting	Support, 0~255, 0 means no limit.
View photo and video	Support thumbnail, 16 times enlargement support video playing, support advanceX2/X4, reteat X2/X4
Display Screen	
Display Screen	2.0 "LCD Screen; definition: 960x480; 16.7M color
Audio	
Microphone	60dB High Sensitivity Sound Collection
Loudspraker	0.5 (8Ω) Hi-Fi Loudspeaker
Audio record	ON/OFF
Boot Sound	ON/OFF
Key Sound	ON/OFF
PIR	
PIR Sensing Angle	Main PIR:50°, 8 zone, each zone 10° Side PIR: Left and right light beams form An angle of 140° left and right of the five zone, each zone 10°
PIR Sensor Distance	20M (at 10°C)
PIR Mode	Main PIR / Main PIR & Side PIR / OFF
PIR Sensitivity	Auto/low/normal/high
Trigger Interval	5-59sec, 1-59min Programmable

HA-TRCAM02

Specification 3



Feature

- Built-in 2G, 3G, 4G GSM wireless image transmission function, SMS / MMS / E-mail
- Support daily report SMS notification
- Support four frequency band quad-band: 850/900/1800/1900mhz.
- With 1/3" high definition 5MP image sensor, Low illumination:0.1Lux (LED off)
- 6.0mm fixed lens. (H FOV=78°, F2.0)
- Photo definition can be optional with 12M/8M/5M/3M/2M/1M
- 1080P/30fps full HD video recording
- Support USB data connection and PC fast parameter settings.
- Support external power supply or solar power, to provide longer working hours.
- Support dismantling chains, protection lock and password protection function, to protect the camera safety.
- Support limit setup for daily shoot numbers.
- Support low power alert.
- Support SD card with maximum capacity of 32G.
- Support the laser alignment, to make more convenient installation.

Model	HA-TRCAM02
Other	
Operation Control	5+1 joystick button, support PC-side software quickly set
Interface	DC input, SD/TF card USB CVBS, mode switch
Mounting	Bandage, tripod nail
Operating	-30°C~+70°C / 30%~90%RH
Storage	-40°C~+85°C / 0%~90%RH
Waterproof Grade	IP68(Dust proof/Submerging test)
Dimension	145.2x91x78.5mm
Net Wight	320g
Gross Wieght	520g
Certificate	FCC,CE

HA-TRCAM02 