

HV-110H

FEATURES

1. Vari-Focal Lens Adjustable Externally
2. With 530 TV Lines Resolution
3. Distance Viewing for 20M
4. Various Angle LED Combination:
 - Uniform IR Light Distribution for optimum viewing angle
5. Double Glass: Effectively Reducing the Internal Reflection
6. Aluminum Alloy Housing for Better Heat dissipation
7. ClassIP65 Weatherproof



SPECIFICATION HV-110H

Pick up device	1/3" interline transfer CCD
Total Pixels	NTSC: 811(H) x 508(V) / PAL: 795(H) x 596(V)
Effective Pixels	NTSC: 768(H) x 494(V) / PAL: 752(H) x 582(V)
Resolution	530 TV lines
Sync. System	2:1 Internal
Scanning System	NTSC: 525 Lines / 60 fields; PAL: 625 Lines / 50 fields
S/N Ratio	More than 48dB (AGC OFF)
Electronic Shutter	Auto 1/60 (1/50) ~ 1/100,000 sec.
Min. Illumination	0.5 lux color / F2.0
Video Output	1.0 Vp-p / 75 ohm composite
IR Distance	20M (28 pcs IR LED)
IR Trigger	3.1lux / 3.7lux IR ON / OFF
Lens Type	Vari Focal Lens: 3.5-8mm
DC Power Source	DC 12V
Power Consumption	6.2W (Max)
Current	520mA (Max)
Weight	N.W./G.W.: 0.76kg / 0.84kg
Dimension	82.5mm(H) x 119mm(Diameter)
Operation Temperature	-10 to 50? (14 to 122?)
Storage Temperature	-20 to 70? (-4 to 158?)

Dimension

