



HV-105S

Main Feature

1/3" Sharp CCD Sensor, 420 TV line,
Lux 0.2/F2.0, Fixed Lens 3.6mm, ATW,BLC
more than 48 dB, Power DC 12 V.



Specification

Model	HV-105S
Image Device	1/3" Sharp CCD Sensor
Scanning Frequency	NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 512(H) X 492(V); PAL: 512(H) X 582(V)
Electronic Shutter	N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto)
Horizontal	420 TV Lines
White-balance	Auto white balance (2500 °K~9500 °K)
Synchronizing System	Internal
Sensitivity	0.2 Lux / F2.0
BLC	Auto
Signal to Noise	More than 48dB AGC off
AGC	Yes
Gamma Correction	0.45
Lens	Fixed Lens 3.6mm
Power Consumption	120mA, +- 5mA
Power Supply	DC 12 V
Temperature	Operating: -10 to 50 °C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	Aluminium
Dimension	75(O) x 110(L) mm