



Main Feature

- High speed: Horizontal: 300°/s
- Tilting: 150°/s
- Support Auto-Flip
- 255 Preset Positions
- 8 Swings, 4 Pattern
- 1 Pan scan, 1 Tilt scan
- 8 Groups, up to 16 presets per group
- Built in Heater & Blower
- 8 Privacy zones
- RS485 Pelco D/P, Auto identify
- Power input: AC24V / 2A
- IP66 waterproof

Specification

Size	1/4 inch, Interline Transfer CCD		
Total Pixels	NTSC: 811(H) X 508(V)	PAL: 795(H) X 596(V)	
Effective Pixels	NTSC: 768(H) X 494(V)	PAL: 752 X 582(V)	
Optics	23X, f=3.5 to 80.9mm (F1.6 ~F2.4)		
Min. Focus Distance	1,500mm		
D.ZOOM	OFF/ON (X2 ~X16)		
Angle field of view	55.5° (Wide) to 2.37° (Tele)		
Scanning System	2:1 Interlace		
Synchronization	Internal / Line-Lock		
Frequency	H: 15.734KHz	V: 59.94 Hz	H: 15.625 KHz V: 50.00 Hz
Resolution	560 TV Line(Min.) : Color (WIDE) / 680 TV Line(Min.) : B/W (WIDE)		
Min. Illumination	0.2 Lux/F1.6 (50 IRE) : Color / 0.02 Lux/F1.6 (50 IRE) : B/W		
S/N	52 dB		
Video Output	CVBS : 1.0Vp-p / 75Ω		
Focus	Auto / Manual / One push		
IRIS Control	Auto , Manual		
Day & Night	Auto, COLOR, B/W(ICR), EXT		
Gain Control	OFF, LOW, MIDDLE, High, MANUAL Selectable		
White Balance	ATW / AWC / INDOOR / OUTDOOR / Manual (1,700°K ~11,000°K)		
Back Light Compensation	OFF / BLC / HLC Selectable		
DRC (Dynamic Range Compression)	OFF / ON		
Electronic shutter speed	AUTO / MANUAL / A.FLK		
SSNR	Low, Middle, High, Off		
Privacy Function	ON / OFF (Depend on the camera function)		
FLIP	Vertical, Horizontal, Vertical-Horizontal, OFF Selectable		
Operating Temperature/ Humidity	-10°C to +50°C / 20% to 80% RH		
Storage Temperature/ Humidity	-20°C to +60°C / 20% to 95% RH		
Dimension	48.6(W) x 53.8(H) x 93.7(D)mm		