

HI-6139

Main Feature

1/3" SHARP CCD Sensor, 600 TV line,
 0.2 Lux , 0 Lux at IR on / F2.0,
 LED 20 pcs. 0 Lux 15M IR On,
 Standard Lens (4,8,12,16 mm Optional).
 more than 48 dB, AWB, BLC Auto,
 Power DC 12V.



Specification



Model	HI-6139 IR Dome Camera
Image Device	1/3" SHARP CCD sensor
Scanning Frequency	NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 811(H) x 508(V); PAL:795(H) x 596(V);
Electronic Shutter	NTSC: 1/60- 1/100,000sec (Auto); PAL: 1/50-1/100,000sec (Auto);
Horizontal	600 TV Lines
White-balance	Auto white balance (2500 °K~9500 °K)
Synchronizing System	Internal
Sensitivity	0.2 Lux , 0 Lux at IR on / F2.0
BLC	Auto
Signal to Noise	More than 48dB (AGC off)
IR Distance	15 Meters (Based on: object of view reflected IR light)
IR LED	High Light LED x 20 pcs
IR Status	500
IR View Angle	View angle: 70 ° Beam spread: 40 °/per LED
IR Wavelength	850nm +- 25nm
LED Life	More than 10,000 hours
Lens	4 mm Standard (4,8,12,16mm option)
Power Consumption	IR on: 180mA, IR off: 120mA (DC 12V) +- 5mA
Power Supply	DC 12V, AC 90V ~ 260V (Auto)
Temperature	Operating: -10 to 50 °C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	Aluminum with sunshield weatherproof
Dimensions	115(W) X 75(H) mm