

HI-7117



Main Feature

1/3" SONY CCD With Cover,
700 TV line, IP68, LED 56 pcs.
0 Lux 25M IR On, Fixed Lens (4,6,8 Option).
Auto Iris, Day& Night, more than 48 dB,
(AWB, BLC Auto), Power DC 12 V.

Specification



| | |
|----------------------|--|
| Model | HI-7117 |
| Image Device | 1/3" SONY CCD sensor |
| Scanning Frequency | NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V) |
| Scanning System | NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace |
| Effective Pixels | PAL: 976(H) X 582(V) |
| Electronic Shutter | N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto) |
| Horizontal | 700 TV Lines |
| White-balance | Auto white balance (2500 °K~9500 °K) |
| Synchronizing System | Internal |
| Sensitivity | 0.1 Lux , 0 Lux at IR on / F2.0 |
| BLC | Auto |
| Signal to Noise | More than 48dB AGC off |
| IR Distance | 25 Meters (Based on: object of view reflected IR light) |
| IR LED | High Light LED x 56 pcs |
| IR View Angle | View angle: 70 ° Beam spread: 40 °/per LED |
| IR Wavelength | 850nm - 25nm |
| LED Life | More than 10,000 hours |
| Lens | Fixed Lens (4,6,8 mm option) |
| Power Consumption | IR on: 500mA, IR off: 80mA (DC 12V) +- 5mA |
| Power Supply | DC 12V |
| Temperature | Operating: -10 to 50 °C |
| Video Output | Composite 1.0 Vp-p at 75 ohm |
| Construction | Aluminum with sunshield weatherproof |
| Dimensions | 95(w) X 90(H) X 160(L) mm |
| Weight | 0.450kg |