



DL9004

H.264 DVR

Features:

1. With 7 inch indash LCD Monitor
2. Standard H.264 video compression, support dual stream network transmission
3. Support D1, HD1 & CIF recording resolution, selectable recording picture quality
4. Graphics & Windows OSD interface, easily to operate with USB mouse
5. With motion detection, sensor triggered and timing recording modes
6. With built-in RS485 port for PTZ control
7. Network: support TCP/IP, DHCP, DDNS, PPPoE
8. Support to backup via USB thumb drive, USB hard disk & USB CD/DVD-RW
9. Support mobile phone surveillance function



Specificaions

Model	DL900
Video Compression	H.264
Video System	NTSC / PAL
Operation System	Linux
Video Input / Output	BNC 4-channel inputs / 1-channel output
Audio Compression	8kHz*16bitADPCM
Audio Input / Output	RCA 4-channel inputs / 2-channel outputs
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Playback Resolution	PAL: CIF(352x288), HD1(704x288), D1(704x576) NTSC: CIF(352x240), HD1(704x240), D1(704x480)
Total Recording Frame Rate	PAL: 25fps@D1, 50fps@HD1, 100fps@CIF NTSC: 30fps@D1, 60fps@HD1, 120fps@CIF
Recording Mode	Always / schedule / motion detection / sensor triggered
Recording Pack Time	15/30/45/60mins selectable
HDD Interface	Support 1 SATA HDD up to 1 TB
Network Interface	RJ45, 10M/100M
Network Protocol	Support TCP/IP, UDP, DHCP, DDNS, PPPoE
Network Function	Support to live view with IE (Internet Explorer) & with Mobile phone
USB2.0	USB mouse, USB disk (backup, upgrade)
Playback Mode	Normal play, fast forward, fast rewind, frame by frame
Backup	Backup file via USB flash disk, USB disk, USB CD/DVD-RW & Network
PTZ Control	Built-in RS485, support PELCO-P & PELCO-D
Mobile Surveillance	Support mobile phones based on Windows Mobile, Symbian S60 3rd, and Iphone
Senor & Alarm I/O	4 sensor inputs / 1 alarm output
Power Supply	DC 12V/3A (power adaptor included)
Power Consumption	10~15W
Working Temperature	-10° C to +40° C
Working Humidity	10% to 90%
Dimension(WxDxH)	515x350x125mm