

HI-6112

Main Features

1/3" Sharp/SONY CCD sensor
650 TV line 0.1 Lux/F2.0 / IP68
LED 48 pcs. 0 Lux 18M IR On
Lens Fix 4,6,8,12 mm.
more than 48 dB,(AGC, BLC Auto)
Power DC 12 / 500mA



Specifications

Model	HI-6112
Image Device	1/3" Sharp/Sony CCD sensor
Scanning Frequency	NTSC:15,734KHz(H), 60Hz(V);PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 811(H) x 508(V); PAL:795(H) x 596(V)
Electronic Shutter	N:1/60- 1/100,000sec (Auto);P:1/50-1/100,000sec (Auto)
Horizontal	650 TV lines
White-balance	Auto white balance (2500 °K~9500 °k)
Synchronizing System	Internal
Sensitivity	0.1 Lux , 0 Lux at IR on / F2.0
BLC	Auto
Signal to Noise	More than 48dB (AGC off)
IR Distance	18 Meters (Based on: object of view reflected IR light)
IR LED	High Light LED x 48 pcs
IR View Angle	View angle: 70 °, Beam spread: 40 °/per LED
IR Wavelength	850nm +- 25nm
LED Life	More than 10,000 hours
Lens	4, 6, 8,12 mm Standard
Power Consumption	IR on: 500mA, IR off: 80mA (DC 12V) \approx 5mA
Power Supply	DC 12V
Temperature	Operating: -10 to 50 °C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	Aluminum with sunshield weatherproof
Dimensions	75(ø) X 110(L) mm
Weight	0.400kg