

HV-722



operation index:

- Level running: 360° continuous revolve, 180° auto flip.
- Rotate speed: 0.5°/S-280°/S level shift, 0.5°/S-280°/S upright shift.
- Tilt rotation range: 90°
- Presets positions quantity: 128pcs program speed and stick time.
- Cruise routes: 8 groups programmable cruise, each group consisting 16 preset positions.
- Scan function: Two points scan can set scan speed and stick time; 360° scan can set scan speed
- Baud rate: 1200/2400/4800/9600 optional .
- Control protocol: multi-protocols, optional .
- Communication: RS485 bus
- Installation option: wall mount, pendant mount, ceiling mount.
- autocontrolled zoom speed: controlled speed is auto-adjusted with the length of zoom.
- Fan , Heater : Fan and heater are controlled auto-intelligently

Specifications:

- New high Die-cast Aluminum Construction, effectively prevent deforming and keep surface bright.
- Newly-designed black shield inner cover, more concealing.
- High quality stepping motor and belt, more reliable.
- Static remove dust, double deck ventilate hole constant temperature design, IP66 weatherproof rating.
- Intelligent speed shift, 0.5°/S-280°/S smooth pan shift, 0.5°/S-180°/S tilt shift, 180° auto flip, 360° continuous revolve.
- 128 preset positions , 8 cruising tracks, each cruising track consisting 16 preset positions.
- Programmable setting cruise speed between presets and presets stick time, 1-64 level cruise speed setting and 1-60 second preset stick time.
- Color 22X optics camera module.
- Built-in multiple protocol, allow any system.
- Power-off information protection and built-in surge, lightning strike protection device.
- Accessory function: Vandal-prevent device.

Model

HV-722

Image sensor	1/4" sony super HAD CCD	IRIS	Auto/Manual
Effective pixel	440 thousands pixel	Black light compensation	On/Off
Resolution	480TVL	Temperature storage	-20 TO 60°
Sync type	Internal/External	Temperature operation	0 TO 50°
Scanning system	2:1 interlace		
Lens	f=3.9~85.8mm	Electrical	
Digital Zoom	22X optical zoom, 10X electronic zoom	• Power supply: 24VAC 3A .	
Horizontal angle of view	47.0°(wide), 3.0° (tele)	• Power consumption: 20W	
Mini illumination	0.5Lux/0.01Lux	Environment	
S/N ratio	>50dB	• Operation Temperature : 0° ~ +40° (Indoor)	
Electronic shutter	1/50 ~ 1/10000s	• -40° ~ +60° (Outdoor)	
Private zone	NO	• Moisture Operation: 0 ~ 95%	
IR	NO		
Color & day / night	YES		
Video Output	1.0±0.2Vp-p 75Ω		
Video Connector	BNC		
Focusing system	Auto/Manual		
White Balance	Auto/Manual		