



**IP CAMERA SERIES**



# **HD IP CAMERA**

**Cube IP Camera**







## Feature

- Introduce high advanced Hi3518C, presenting vivid and clear image with low power.
- Low illumination, 0.6Lux @ (F1.2, AGC ON), 0 LUX with IR
- Support IR-CUT, realising day&night non-stop monitoring.
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support TF card local storage.
- Support two-way audio, support dual-stream.
- Plug and Play, multiple Network Cloud security and surveillance
- support various mobile long-distance monitoring, iPhone, Windows Mobile, BlackBerry, Symbian, Android
- Support multiple web browsers, IE, Chrome, Firefox, Safari
- Support WIFI, only apply to-W type
- support auto electronic shutter, adapt to different monitoring environment. web and CMS supporting, central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF.

## Specification

Model	Hmc-cube01
Camera	
Image sensor	1/4" OV 09712 CMOS
Min.illumination	Color: 0.6Lux @(F1.2,AGC ON),0 LUX with IR B/W: 0.08 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s to 1/10,000 s
Lens	Professional lens 4mm@F2.0
Lens mount	M12
Day/night	Support IR-CUT
Compression	
Video compression	H.264 HighProfile, JPEG snapshot
Bite rate	32 Kbps~8Mbps
Audio compression	G.711a
Image	
Max.image reolution	1280x960
Frame rate	50Hz:25fps(1280*960) 60Hz:30fps(1280*960)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client software.
Network	
Storage	TF storage, Network storage
protocol	HTTP, TCP/IP, UDP, RTSP etc...
intelligent alarm	Motion detection, video loss, cable break, IP address conflicts, memory full, memory error
Basic	one-key reset, anti-flicker, dual-stream, heartbeat, password protection
Wireless Network	Support
Interface	
Network interface	1xRJ45 10M/100M
Audio Input / output	1ch. Micro port / 1ch. 3.5mm JACK port
Wifi	Built-in WIFI 802.11g/b/n
Alarm Input/Output	1ch. / 1 ch.
Other	
Working condition	-10 <sup>0</sup> C ~ +60 <sup>0</sup> C humidity less than 90% ( non-condensing)
Power supply	DC5V +10%
Power consumption	IR3 : 5W MAX;
IR distance	“IR1”:10-20 meters;
Dimension	74mm*128mm*57mm
Weight	500g