

Hi-6522

Feature

Image Sensor 1/3"SONY Exview HAD CCD
 Lens f=3.9~85.8mm, Optical Zoom 30X
 Resolution 650TVL (Color), 700TV L(B/W)
 Mini. Illumination 0.2 LUX (Color), 0.01 LUX (B/W)
 Function: White Balance, ICR (Auto/Day/Night), PTZ Mode
 3D Positioning. Power Supply DC 12V.



Specification

Image Sensor	1/3"SONY Exview HAD CCD
Lens	f=3.9~85.8mm
Optical Zoom	30X
Resolution	650TVL (Color), 700TV L(B/W)
Mini. Illumination	0.2 LUX (Color), 0.01 LUX (B/W)
Electronic Shutter	1/50~1/10,000s
White Balance	Auto/ATW/BLC/Indoor/Outdoor/Manual
Day/Night	ICR (Auto/Day/Night)
S/N Ratio	≥52dB
Video Output	1.0V [p-p] /75Ω , NTSC (or PAL) composite, BNC
Pan/Tilt Rotate Speed	Horizontal: 0°~600°/s , Vertical: 0.01°~120°/s
Pan/Tilt Rotate Range	Pan Range: 360° continuous rotation, Tilt Range: 0°~90° with auto flip
Manual Control Speed	600°/s
Preset Speed	600°/s
Preset	255
PTZ Mode	8 auto scan, 8 auto tour, 4 groups of pattern
3D Positioning	Yes
Info Display	Time, Location, Dome title, Dome coordinates, Temperature, Alarm, and etc.
Power Up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate preset/scan/tour/ patter if there is no command in the specified period
Time Task	Auto activation of Preset/Scan/Tour/ Pattern by preset-time
Alarm	7inputs/2outputs
Protocol	HS, PELCO-D, PELCO-P, Auto recognition of general protocols
Baud Rate	2400/4800/9600bps
Power Supply	DC12V+~10%/4A
Power Consumption	50W
Working Temperature	Outdoor: (-35℃~+60℃)
Working Humidity	0~95%(No condensation)
Protection Level	IP66
Weight	5.8KG

