



NVR

8800SERIES



NVR CCTV Surveillance

Network Video Recorder

H.264



HDMI



USB



IP PTZ

FREE
DDNS



IVS



Cloud

รายละเอียดสินค้า



คุณสมบัติหลัก

- Step on the Internet: With XM cloud service, easy to achieve a variety of network penetration, one step to remote monitoring.
- Ideal Compression algorithm: H.264 High Profile compression algorithm, 30% decrease of stream due to advanced space-time filtering technology.
- Mobile monitor: Support various mobile monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android), support 3G/4G and WIFI module extension.
- Display: Support TV, HD, VGA and HDMI output simultaneously (VGA, HDMI support 1080P HD output), overturn traditional monitoring thoroughly.
- Operation interface: Similar to CMS operating style, easy to get started with powerful mouse right-click function.
- Network: Powerful network services (support DHCP, PPPoE, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP permissions, IP searches, Alarm Center, etc.) and perfect support (WEB, Client, SDK), easy to achieve interoperability.
- Browsers: Support IE, Chrome, Firefox, Safari browsers.
- Remote Access: With its own domain name service functions (ARSP), and one key to remote monitoring, monitoring becomes easy and enjoyable. 3322 (Greek network), dyndns, oray (peanut shells), myq-see and other Domain Name Services are also provided.
- Device port: support 2* SATA5 ports (Max 4T), 1* SATA port, 2* USB 2.0 ports, easy to carry out USB mouse, backup, burning, upgrading and other operations.
- Differentiation: Boot screen free replacement, more than twenty languages, over 10 sets of GUI interface, ten kinds of remote control, available in dozens of button panel, which make our products different from others.
- Others: Perfect circuit protection, unique triple watchdog function, ensure that the equipment never crashes. With unique black box technology, the whole process can be monitored, which greatly reduces maintenance costs.

รุ่น	Hmp-8816N
System	
ระบบปฏิบัติการ	Linux System.
System resources	Simultaneous multi-channel real-time recording, playback, network operation backup
Interface	
User interface	Support 16-bit true color graphical menu interface and mouse operation
การแสดงผลภาพ	1/4/8/9/16
Vedio	
ระบบภาพ	PAL (625line, 50I/s) ; NTSC (525line, 60I/s)
การบีบอัดภาพ	H.264 (High Profile)
ความละเอียดภาพ	D1&VGA:HD / HDMI:HD
เลนส์อินฟราเรด	Up to 1/2Ch.@1080P Mode/ 4ch.@720P Mode
Video access	8*5M /16*3M /24*1080P /32*960P
ตรวจสอบความเคลื่อนไหว	Support
Audio	
การบีบอัดเสียง	G.711A
Bidirectional talk	Support
Record&playback	
โหมดการบันทึก	Manual/Alarm/Motion/Detection/Continuous.
ความละเอียดภาพ	3M/1080P/720P
โหมดค้นหา	Time/Date/Alarm/Motion.
Storage&backup	
ปริมาณพื้นที่การบันทึก	Video: CIF 4-5G./day/ch, D1 8-10G./day/ch, 960H 12-20G./day/ch, 720P 24-30G./day/ch, 1080P 40-100G./day/ch ; Audio : 691.2M./day/ch
พื้นที่จัดเก็บ	HDD, Network
โหมดแบ็กอัพ	Network backup, USB HDD, USB writer, SATA writer
Interface	
5V โอ อินพุต	4ch@3M / 8ch@1080P / 16@1080P
5V โอ เอ้าท์พุท	1ch VGA, 1ch HDMI
ออดีโอ อินพุต	1ch RCA
ออดีโอ เอ้าท์พุท	1ch RCA
อะลาร์ม อินพุต	N/A
อะลาร์ม เอ้าท์พุท	N/A
ช่องเชื่อมต่อ	1*RJ45 10M/100M
เชื่อมต่อการควบคุม	1*RS485 : support multiple PTZ protocols
USB	2*USB2.0 / 1*USB3.0
ฮาร์ดดิสก์	2*SATA ports (Max 4T per pcs)
Onvif	Support
Other	
ไฟเลี้ยง	220V AC / 12V DC
ขนาด	350mm(L)* 295mm(W)* 45mm(H)

NVR8800 Series NETWORK CCTV Surveillance

การรับประกันสินค้าในกรณีนี้จะมีอายุ 3 ปี โดยไม่มีค่าใช้จ่ายใดๆ

