



NVR

HP-9716H2



NVR SURVEILLANCE

Network Video Recorder



Specification



Feature

- NVR 16ch.,H.264/H.265, Linux
- Network IP input 16ch. /160Mbps bandwidth
- Resolution support 5MP,4MP,3MP,1080P,960P,720P,@25fps/30fps.
- Output resolution HDMIx1(4Kx2K/1920x1080/1280x1024)
- VGAx1(1920x1080/1280x1024)
- Audio input RCA x1(2-way audio), Audio output RCAx1
- Dual Stream,RJ45x1(10/100/1000Mbps),SATAx2(Max10Tb/pc),USB 2.0x1,USB 3.0x1
- Protocol TCP/IP,PPPoE,DHCP,DNS,DDNS,UPnP,NTP,SMTP
- Playback Max 16ch.,Network playback x16
- Web client max 10 user, APP,P2P,QR CODE,NAT,LOG,IE,CMS
- Support PTZ 255preset and 8 cruises.
- Power input DC12V, /Consumption <15W(without HDD)
- Work Environment -10C~+50C, 10%~90% Humidity

Model	HP-9716H2
Compression	Standard H.265/H.264
OS	Embedded Linux
Video	
Network Input	16 CH IPC input
Network Access Bandwidth	160Mbps
Network Access Format	5MP/4MP/3MP/1080P/960P/720P@25/30fps
Output	HDMIx1:4Kx2K/1920x1080x1280x1024 VGAx1:1920x1080/1280x1024
Audio	
2-way Audio	RCAx1
Local Output	RCAx1
Record	
Record Stream	Dual stream recording
Resolution	5MP/4MP/3MP/1080P/960P/720P
Mode	Manual,timer,motion,sensor
Playback	
Simultaneous Playback	Max 16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play,pause,FF,FB,digital zoom,etc.
Alarm	
Mode	Manual,sensor,motion,exception
Input	Support IPC alarm input
Output	Support IPC alarm output
Triggering	Record,snap,preset,e-mail,etc.
Network	
Interface	RJ4510/100/1000 Mbpsx1
Protocol	TCP/IP,PPPoE,DHCP,DNS,DDNS,UPnP,NTP,SMTP
Web Client	Max 10 users online
Mobile Device	
OS	iOS,Andriod
Storage	
HDD	SATAx2, max 10Tper HDD
Backup	
Local Backup	Udisk,USB mobile HDD
Network Backup	Yes
USB	USB2.0x1(front panel),USB3.0x1(rear panel)
Remote Controller	Optional
Power Supply	DC 12V
Consumption	≤15W (without HDD)
Dimensions (mm)	430x300x55 (WxDxH)
Work Environment	-10 ~ 50C, 10% ~ 90% humidity