



**NEW** **STAR LIGHT**  
กล้องสตาร์ไลท์ เปลี่ยนกลางคืนให้เป็นกลางวัน

กลางวัน กล้องสตาร์ไลท์      กลางคืน กล้องสตาร์ไลท์

# **HD** **AHD CAMERA SERIES** *CCTV SURVEILLANCE* **Star Light Camera**

### Specification



### Function

- Function control OSD (COC control)
- OSD language Support English, Etc. adjustable
- Global exposure/ COC Support
- D-WDR / AGC / Sens-Up / BLC Support
- HSBLG Support / Ultra-WDR Support (120dB)
- ATW / AWB / 2D-DNR / 3D-DNR Support
- Brightness / Defogging / Cam title Support
- Freeze / Mirror Support
- Neg. image / Motion detection Support
- Privacy mask Support
- Defect Support (Live DPC, White DPC, Black DPC)
- Sharpness / LSC Support
- Image setting Support  
(Black level, Gamma, Blue gain, Red gain)

Model	HA-924B20ST
Solution	1/2.8" Sony CMOS progressive scan Sensor
Video system	4-in-1 (AHD/TVI/CVI/CVBS)
Video format	PAL/NTSC
Video resolution	1920x1080P
Effective pixel	2.13MP.
CVBS resolution	960H CVBS output (1000TVL)
CVBS Comet	Support
Min. illumination	Color: 0.001 lux@F1.2, AGC ON, B/W: 0 lux with IR ON
Electric shutter	Auto:1/25s to 1/100,000s (PAL), Auto: 1/60s to 1/100,000s (NTSC)
Frame rate	30fps@60Hz, 25fps@50Hz
S/N ratio	>52dB. (AGC OFF)
Ingress protection	IP66
<b>Lens</b>	
Lens size / F.No.	2.8mm. / F1.2
Lens mount	M12
<b>Infrared</b>	
IR type	IR LED 42 Pcs.
IR distance	20-30M.
Day&Night	Support color, B/W, Auto, Ext adjustable
ICR switch	Support IR filter (IR-CUT)
IR smart	Support adjustable
<b>Hardware interface</b>	
Video output	BNC female x1
Power input	DC Jack x1
Cable	Switch Cabel
<b>Electrical</b>	
Power supply	DC12V(+/-10%)
Power consumption	IR OFF: <1W., IR ON: <4W.
<b>Others</b>	
Surge protection	4KV, Anto static 6KV(touch), 8KV(Gas)
Working environment	-30°C to -60°C
Working humidity	10% to 90%
Dimension / Weight	87x219.4mm. / 537g.