hi-view®

Geraral Specification (Wi-Fi Presentation System)

Video Output	HDMI 1.4, Comply with "HDCP"
Frame Rate	Up to 30fps (depending on environment)
Output Resolution	1920x1080, 1280x720, 800x600, 960z960, 1024x768 1360x768, 1440x900, 1440x1050, 1680x1050
Input Resolution	Up to1920x1080
Audio	Stereo, Radio quality 16 bit 48KHz
Wireless	IEEE 802.11ac, 5GHz, 2T2R
Authentication Protocol	WPA2 (WPA2-PSK (Pre-Shared key)
Distance	Max. 10-20 Meters. (Between RX and TX)
Transmission	Audio/video
Operating	0°C to +40 °C (+32°F to +104°F)
Storange	-10°C to +60°C (+14°F to +140°F)
Operating Humidity	10% to 80%

Model: WPS-1080T, WPS-1080R
1 Set (TX x2Pcs., RS x1Pcs.)

One Button Sync to Large Screen Display For All Devices
Wireless Presentation System
Switch Screen Easily, Suitable for High Profile Meetings.

Products Features
- No configuration, no manual setting or installations required.
- Low budget, Eliminate cables, save money from expensive layout of hidden cable.
- Support Full HD 1080P.
- High compatibility, All devices with HDMI output, PCs, Notebooks/laptops
  TV boxes, smartphones or tablets.
- The idea comes from traffic light.
     Red (activating).
     Flashing (red-error).
     Bright orange (standby).
     Green(sharing).
     Flashing green(pairing).
     Blue-(VIP).

TX (Model WPS-1080T)

Color	White
Function Button	x1
Reset Button	x1
Video Input	x1 (HDMI 1.4)
DC Power Jack	x1 (micro USB)
LED light	LED 4 colors: R/Y/G/B
	Red: bright red - booting flashing red - error
	Orange: bright orange-idle
	Green: Bright green - in projection Flash green - in pairing
	Blue: Bright Blue - VIP Projection Flash Blue - VIP Pairing
Latency	<100ms
Power Rating	5VDC±10% /0.9A.
Dimension	Φ90 x H25mm.
Weight	90g.
HDMI Cable	x1 (30cm.)
USB Power Cable	x1 (30cm, USB Type A 3.0, micro USB)

RX (Model WPS-1080R)

Color	Black
Max. Receiver	Up to 64 (Can connect to WPS-1080T max. 64 pcs.)
Function Button	x1
Reset Button	x1
Video Output	x1 (HDMI 1.4)
DC Power Jack	x1 (micro USB)
LED light	LED 4 colors: R/Y/G/B
	Red: bright red - booting flashing red - error
	Orange: bright orange-idle
	Green: Bright green - in projection Flash green - in pairing
	Blue: Bright Blue - VIP Projection Flash Blue - VIP Pairing
Latency	<100ms
USB Power Cable	x1 (150cm, USB Type A 3.0, micro USB)
Antenna Jack	x2
Power Rating	5VDC±10%/1.5A
Dimension	Φ90 x H25mm. (95mm with antenna)
Weight	100g.
HDMI Cable	x1 (80cm)
Antenna	x2 (Black)
Adapter	x1
Velcro Strap (Black)	x1
Quick Start Guide	x1
Bracket	x1
Screws	x4

Remark
-Please read the manual carefully to understand the LED indicator number.
-Wireless transmission speed varies depending on the on-site wireless network environment