



Main Feature

- Standard H.264 video compression.
- Touch Front Panel
- Monitor display support AV and VGA.
- Support multiplex operation on live display, record, playback, backup and network.
- Support edit the recorded video file and select a specific range of time.
- Support alarm events by email.
- Supports online connection on mobile smartphone.

Specification

| | | |
|-----------------------|-------------------|---|
| Video / Audio inputs | Video | 8 ch, BNC (1.0Vp-p, 75Ω), PAL/NTSC auto |
| | Audio | 1 ch RCA (2.0Vp-p, 1kΩ) |
| Video / Audio outputs | video | 2 ch, BNC (1.0Vp-p, 75Ω) |
| | Resolution | PAL: 704*576, NTSC: 704*480 |
| | Audio | 1 ch, RCA (lining, 600Ω) |
| | VGA | 1 ch, Resolution: 800*600, 1024*768, 1280*1024 |
| | HDMI | - |
| A / V decoder | Compression | H.264 |
| | Decoder | resolution D1 base (D1/HD1/CIF) |
| | Video Frame | PAL: HD1: 25fps, NTSC: 30fps / EACH CHANNEL |
| | Video Rate | Image Quality adjustable, Adjustable Rate, fixed Rate optional |
| | Stream | Multiple |
| | Audio compression | G.711A |
| | Playback | 1/4/9 ch at the same time |
| | Display | Support S.E.Q., PIP, ZOOM |
| Record | Mode | Continuous/Manual/Motion detect /Sensor/Alarm recording |
| | Save | HDD, PC Remote save, and Mobile save |
| | Back up | USB port savers (Pen Driver, Removable HDD & DVD-RW), Remote Back up (like PC, Mobiles) |
| HDD | Port | SATA x1 |
| | Capabiltiy | 2TB |
| Network | Functions | Live view, Remote control, remote settings via PC and Mobile |
| | Protocol | TCPIP/ UDP/DHCP/DDNS/PPPoE |
| Accessories Port | Port | RJ45 10M/100M |
| | RS ports | standard RS-485 port for PELCO-P and PELCO-D |
| | USB | USB 2.0 x3 (Back 2pcs / Front 1pcs) |
| | Alarm inputs | - |
| | Alarm Output | - |
| | IR-ex | - |
| Sensor & Alarm | | - |