



Main Feature

- Standard H.264 video compression.
- Touch Front Panel
- Monitor display support AV and VGA.
- Support multiplex operation on live display, record, playback, backup and network.
- Support edit the recorded video file and select a specific range of time.
- Support alarm events by email.
- Supports online connection on mobile smartphone.

Specification

Video / Audio inputs	Video	16 ch, BNC (1.0Vp-p, 75Ω), PAL/NTSC auto
	Audio	4 ch RCA (2.0Vp-p, 1kΩ)
Video / Audio outputs	video	1 ch, BNC (1.0Vp-p, 75Ω)
	Resolution	PAL: 704*576, NTSC: 704*480
	Audio	1 ch, RCA (lining, 600Ω)
	VGA	1 ch, Resolution: 800*600, 1024*768, 1280*1024
	HDMI	Yes
A / V decoder	Compression	H.264
	Decoder	resolution D1 base (D1/HD1/CIF)
	Video Frame	PAL: HD1: 25fps, NTSC: 30fps / EACH CHANNEL
	Video Rate	Image Quality adjustable, Adjustable Rate, fixed Rate optional
	Stream	Multiple
	Audio compression	G.711A
	Playback	1/4/9/16 ch at the same time
	Display	Support S.E.Q., PIP, ZOOM
Record	Mode	Continuous/Manual/Motion detect /Sensor/Alarm recording
	Save	HDD, PC Remote save, and Mobile save
	Back up	USB port savers (Pen Driver, Removable HDD & DVD-RW), Remote Back up (like PC, Mobiles)
HDD	Port	SATA x1
	Capabiltiy	2TB
Network	Functions	Live view, Remote control, remote settings via PC and Mobile
	Protocol	TCPIP/ UDP/DHCP/DDNS/PPPoE
Accessories Port	Port	RJ45 10M/100M
	RS ports	standard RS-485 port for PELCO-P and PELCO-D
	USB	USB 2.0 x3 (Back 2pcs / Front 1pcs)
	Alarm inputs	-
	Alarm Output	-
	IR-ex	-
Sensor & Alarm		8ch Sensor Inputs & 1ch Alarm Output