

PLUS+
YOUR
Power by *Azking*



YP2-101B

4IN1SYSTEM

AHD TVI CVI ANALOG SUPPORT

FULL HD

- FULL HD Video Output
- 4in1 AHD TVI CVI Analog
- LED Smart IR 18Pcs.
- Day&Night IR CUT



PLUS+ YOUR

Power by *Azking*



Feature

- 1/2.7 SmartSens SC2235 CMOS sensor
- Video Resolution 1920x1080P
- Min. Illumination Color: 0.1 lux@(F2.0, AGC ON), 0 lux with IR
B/W: 0.01 lux@(F2.0, AGC ON), 0 lux with IR
- Lens size 3.6mm.
- IR SMD 18 pcs., Up to 30M., Smart IR
- IR CUT (IR Filters)
- WDR, BLC, ATW, Anti Flicker
- IP66
- Power supply 12VDC

4IN1SYSTEM

AHD TVI CVI ANALOG SUPPORT

Specification

Model	YP2-101B
Solution	1/2.7 SmartSens SC2235 CMOS sensor
DSP	XM330
Video Resolution	1920x1080P
Video system	4-in-1 (AHD/TVI/CVI,CVBS)
Scan	CMOS progressive scan
Video format	PAL/NTSC
Synchronous Mode	inter-sync
Min. illumination	Color: 0.1 lux@(F2.0, AGC ON), 0 lux with IR B/W: 0.01 lux@(F2.0, AGC ON), 0 lux with IR
Electric shutter	1/50(1/60)s to 1/100,000s
S/N ratio	>58dB
Ingress protection	IP66
Lens	
Lens size	3.6mm.
F/No.	F2.0
Lens mount	M12
Infrared	
IR type	IR SMD 18 Pcs.
IR distance	10-30M.
Day&Night	Support color, B/W, Auto, Ext adjustable
ICR Siwtch	Support IR filter (IR-CUT)
IR Smart	Support
ICR Swap control	Support
Function	
OSD Menu	Support
COC	Support
XVI Control	Support
Grobal exposure	Support
Brightness	Support (adjustable)
Contrast	Support (adjustable)
Saturation	Support (adjustable)
Hue	Support (adjustable)
Sharpness	Support (adjustable)
Mirror	Support
Flip	Support
Image style	Support (adjustable)
Anti Morire	Support
BW Burst	Support
Anti Flicker	Support
Backlight	Support
Denoise (DNR)	Support (adjustable)
WDR	Support
BLC	Support
ATW	Support
Hardware interface	
Video output	BNC female x1 (1.0 Vp-p Composite (75Ω))
Power input	DC Jack x1
Electrical	
Power supply	DC12V(+/-10%)
Power consumption IR Off	1.4W.
Power consumption IR On	5.3W.
Others	
Surge protection	4KV
Working environment	.-10°C to +60°C
Working humidity	10% to 90%
Casing material	Metal white bullet
Weight	295g.