

HI-6112



Mian Features

1/3" SONY CCD sensor With cover,
 650 TV line 0.1 Lux/F2.0 / IP68
 LED 48 pcs. 0 Lux 18M IR On
 6 Standard Lens (4,8,12 mm Option).
 Auto Iris, more than 48 dB,
 (ATW, BLC Auto), Power DC 12V 500mA

Specification



| | |
|----------------------|--|
| Model | HV-6112 |
| Image Device | 1/3" SONY CCD sensor |
| Scanning Frequency | NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V) |
| Scanning System | NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace |
| Effective Pixels | N/A |
| Electronic Shutter | N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto) |
| Horizontal | 650 TV Lines |
| White-balance | Auto white balance (2500 °K~9500 °K) |
| Synchronizing System | Internal |
| Sensitivity | 0.1 Lux , 0 Lux at IR on / F2.0 |
| BLC | Auto |
| Signal to Noise | More than 48dB AGC off |
| AGC | Yes |
| Gamma Correction | 0.45 |
| IR Distance | 18 Meters (Max.) |
| IR LED | 68 pcs LED |
| IR Status | Under 1 0 Lux by CDS auto control |
| IR View Angle | View angle: 70 ° Beam spread: 40 °/per LED |
| IR Wavelength | 850nm - 25nm |
| LED Life | More than 10,000 hours |
| Lens | 6 Standard Lens (4,8,12 mm Option), AUTO IRIS |
| Power Consumption | IR on: 1A, IR off: 70mA +- 5mA |
| Power Supply | 12VDC, 110V ~ 240AC |
| Temperature | Operating: -10 to 50 °C |
| Video Output | Composite 1.0 Vp-p at 75 ohm |
| Construction | Aluminum |
| Dimensions | 75(φ) X 110(L) mm |