

HI-7042



Feature

- SONY 1/3" Super HAD II CCD Sensor
- DSP SONY Effio-E
- Resolution 700 TVL
- Min illumination 0.0Lux (with IR on)
- LED Array 2 pcs, IR Range 25-35m
- Function White Balance, OSD Menu, AGC
- 3 AXIS Bracket, IP 66
- Power DC12V-24V, DC12V/AC24V



Specification

IR CAMERA SERIES High Resolution 700TVL IR

TV System	NTSC / PAL	ATR	-
CCD Sensor	SONY 1/3" Super HAD II CCD	Motion Detection	OFF / ON
DSP	SONY Effio-E	Privacy Masking	OFF / ON
Effective Pixel	976(H)x494(V) 976 (H)x582 (V)	Mirror	ON / OFF (Left/Right)
Scan	2:1 Interlace	NR	2DNR
SNYC System	Internal / External	Sharpness	1 - 255 A djustable
Resolution	700 TVL	Menu Language	Chinese / English / Japanese / German / French , Russian / Portuguese / Spanish
Video Output	BNC 1.0Vp-p75ohm	Lens	4mm, 6mm
Burst Level	0.286Vp-p	Angle of View	73.74° ~ 53.13°
S/N Ratio	>52dB	Lens Mount	CS
Minimum Illumination	0.0 Lux (with IR on)	Power Supply	DC12V-24V, Support DC12V/AC24V - Dual Voltage Power Supply
Electronic Shutter	Auto / Manual	Power Consumption	Max. 1W (Max. 7 W with IR Cut Filter ON)
Expose Control	AES / DC Drive Auto Iris / Video Drive Auto Iris Auto / Manual / AIS	Operating Conditions	-20°C ~ 50°C
White Balance	ATW / Push / USER1 / User2 / Manual / Push Lock	IR Light	2 pcs of IR A rray LEDs (2.5 W Each)
AGC	Auto / Manual	IR Range	Up to 25-35 m
OSD	Yes (Cover-Opened Adjustment)	Weather Proof	IP66
D/N Switch	Auto / Color / Black & White / EXT1/ EXT2	Bracket	3-AXIS Concealed Cable Bracket
IR	Smart IR	Dimension	178.2 mmx 64.5 mmx 76.5mm
BLC	OFF / BLC / HLC	Weight	530g
HLC	-		
Image	Mirror/Lightness/Contrast/Sharpness/Color/Gain		
E-zoom	-		
Digital Image Stabilizer	-		
Digital WDR	OFF / ON 128xWDR (52dB)		
WDR	-		
Flicker- Less	-		

Dimension:

