



# IP CAMERA HP-55B10





Specification

System	Embedded RTOS design,dual core 32-bit DSP(HI 3518E)
Sensor	1/3 " OV9712 CMOS sensor
Video	H.264 main profile,support dual stream,AVI format;support 0.1M~6Mbps bit rate adjustable;support 1~30fps adjust
Resolution	Mainstream:1280*720Sub stream:704*576 ;
Network	1 * RJ45, 10/100M; Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
Auto Iris	1 * Auto Iris port,support DC driver auto iris camera
Photoresistor	1 * photoresistor port, support photoresistor input signal actived with picture,IRCAT and IR light
CVBS video output	Support CVBS video output and overlying DDNS,user name,password and other info.
3G	NO
WIFI	NO
Basic function	Support WEB remote config,OSD,motion detect,alarm input actived to record,snapshot (MJPEG),CMS,mobile software(iPhone Blackberry,Android,Symbian and windows), MYEYE(multiple devices management system), SDK
ONVIF	Support
Mobile	Support (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
lens	2.8MM
IR	24Pcs Φ5mm IR Leds
IR Distance	10-15 Meter
Weight	0.5KG
Power Supply	12V DC stabilivolt/>1000mA
Waterproof level	IP66
SIZE	148*63



Feature

- Support IR-CUT,with ICR and automatic color change to achieve day/night function.
- Advanced design, three-axis rotation, high reliability.
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality. Support HVR/NVR,Support Onvif 2.2
- Plug and Play,multiple Network Cloud security and surveillance.
- Support various mobile long-distance monitoring iPhone, Windows Mobile, BlackBerry, Symbian, Android Support multiple web browser (IE, Chrome, Firefox, Safari)
- Support auto electronic shutter, adapt to different monitoring environment